

PRATICA

PROFESSIONAL GRINDER | MACINACAFFÈ PROFESSIONALE

TECHNICAL DATA | DATI TECNICI

| | | |
|-----------------------------|-----------------------------|--|
| Order code | Codice materiale | AE 65 2.4B |
| Voltage / Frequency / Phase | Tensione / Frequenza / Fase | 100 / 50 / 1 |
| | | 100 / 60 / 1 |
| | | 110-127 / 60 / 1 |
| | | 220-240 / 50 / 1 |
| Max. nominal power | Max. Potenza nominale | 220-240 V drive: 440 W |
| | | 100 V drive: 510 W |
| | | 110-127 V drive: 580 W |
| RPM | Giri motore | 1400 rpm (50 Hz) 1700 rpm (60 Hz) |
| Grinding capacity | Capacità macinazione | 4-5 g/s @ 250 µm (50 Hz) 5-6 g/s @ 250 µm (60 Hz) |

CERTIFICATIONS | CERTIFICAZIONI

CE, (CB), ETL Safety, ETL Sanitation,
 Conforms to Conforme a:
 EC/EN 60335-1 except IPX1; IEC/EN 60335-2-64 except IPX1
 Certified to Certificazione:
 Standard ANSI/UL 763; CSA C22.2 No. 195; NSF / ANSI 8

COLOR OPTIONS | ALTRI COLORI SU RICHIESTA

Black/Grey
 Other colors on request


Nero/Grigio
 Altri colori su richiesta




Other elec. specifications available on request | Voltaggi speciali a richiesta

 Ø 65 mm
 Hardened steel
 Acciaio temperato

 1.2 kg

 195 × 578 × 387 mm

 11.2 kg Net | Netto
 12.7 kg Gross | Lordo